

ES(ENE

HD

Hotel Compact Type IP Phone

HS118V2



HS118V2 hotel IP phone can satisfy most hotel rooms and even the application requirements, beside, it has good expansibility and clear characteristics of quality voice calls.

HS118V2 is a popular type IP Phone in hotel phones series, with modern design, functional, practical and voice clarity characteristics. It accomplished the powerful telephony features by cooperating with the communications platform, such as call transfer, hotline, multi-party conferences, voice mail, interruption-free, etc.

HS118V2 IP phones support defined 10 programmable keys ,and it can define according to the hotel different needs. such as hotel all kind of equipment sevice hotline (housekeeping, ticketing, switchboard, food and beverage, etc.), the hotel special features (alarm clock, voice mail, etc.)

Key Features

- Support 10 programmable keys.
- HD Voice: HD Codec, HD Speaker.
- WEB support Multi-language, e.g. Chinese, English, Russian, French etc.
- One SIP accounts and support three-way conference.
- Support IEEE802.3af class 0(POE).
- Convenient and fast for Installation and maintenance
Support HTTP/TFTP/Telnet/Auto provision.
- Call hold, Call waiting, Call forward, Call return,Call transfer.

HS118V2 Technical Datasheet

Phone Features

2 SIP accounts, Hotline
Call hold, Call waiting, Call forward, Call return, Redial, Mute, DND
Call transfer (blind/busy/ask)
Auto-answer, 3-way conferencing
Speed dial, SMS, Voicemail
Message Waiting Indication LED
Tone scheme, Volume control
Direct IP call without SIP proxy
Ring tone selection/import/delete
Phonebook, Black list, Hand-free indicator.
Call history: Multi-Language
Support switching SIP server & Second server
10 programmable keys

Advanced Features

XML Phone Book search and input & output
Enterprise phone book(800 entries)
LDAP phone book
Functions customizable keys

IP PBX System Integration

DND ; Forward synchronization
Intercom, Paging, Music on hold
Call pickup, Dial Plan,
Call recording Anonymous call,
Anonymous call rejection

Codes and Voice Features

Wideband Codec: G.722
Narrowband codec: G.711μ/A, G.723.1
G.726, G.729AB,iLBC
VAD, CNG, AEC, AGC, Full-duplex,

Security

VLAN QoS (802.1pq).
Phone lock for personal privacy protection
Admin/User 2-level configuration mode , LLDP, CDP
L2TP VPN tunneling protocol - added

Network Features

SIP v1 (RFC2543), v2 (RFC3261)
SIP connection: Proxy mode & Peering Points mode;
DNS SRV (RFC3263);
Redundant server support
NAT Traversal: STUN mode
DTMF: In-Band, RFC2833, SIP Info, Auto
HTTP/HTTPS Web Management
IP Assignment: Static/DHCP/PPPoE
Bridge/Router mode for PC port
TFTP/DHCP/PPPoE client
DNS client, NAT/DHCP server
Layer 3 ToS, DSCP

Management

Auto-provision via FTP/TFTP/HTTP/HTTPS
Configuration:
browser/phone/auto-provision
Trace package and system log export

Physical Features

30keys, including 12 digital keys
10x programmable keys, 1x redial key, 1x hold key, 1x speaker key, 1x flash key, 1x mute key
1x message LED
1x RJ-9 handset port
1xRJ45 10/100M Ethernet ports
Power over Ethernet ,IEEE 802.3af,class 0
Operating humidity: 10~95%
Storage temperature: up to 60°C
Power adapter: AC 100~240V input and DC 5V/1A output

Package Features

Qty/CTN:
N.W/CTN:
Carton Meas:

Certifications



Compatible with the platform



ES CENE COMMUNICATION CO.,LTD

Add: Floor 4 building C YueAn Industrial Park No.51 Huangcun Road Tianhe District,Guangzhou,China.

Tel: (86)20-82320720 Fax: (86)20-82326757